



P120i

VALUE



P120i Card Printer

Key Features

- » 30 Sec/Card Full-Color, Single-Sided Print Speed
- » 35 Sec/Card Full-Color, Dual-Sided Print Speed
- » 100 Card-Capacity Feeder
- » 16-digit LCD Display
- » USB Communication
- » CardSense™ Single Card-Feed (Optional)
- » 3 Track Magnetic Encoder (Optional)

Advanced Design Delivers the World's First Dual-sided, Compact Card Printer at an Unprecedented Price

The P120i's versatility and affordability make this printer the smart choice for savvy buyers. From IDs to access control cards to gift cards, Zebra's P120i delivers big ideas at a small price.

Use the P120i card printer for:

- » Employee ID and Access cards
- » Student and Faculty ID's
- » Membership cards
- » Personalized Loyalty and Gift cards

Zebra P120i Advantages

Versatile: Print single-sided or dual-sided; Monochrome or full-color; Automatic card-feed or CardSense™ single card-feed.

Easy-to-Use: Small; Lightweight; Reliable; 16-Character LCD display; Blue touch-points; Translucent card-cover; Toolless printhead replacement.

Economical: Most-affordable dual-sided printer.

Innovative Patent-Pending Technology: Compact design based on integrated card feeder and flipper; Easy to replace Load-N-Go™ ribbon cartridge with integrated card-cleaning roller.



**Card
Printer
Solutions**

P120i

Card Printer Product Specifications



General Specifications

- » Integrated feeder-and-flipper
- » Load-N-Go™ drop-in ribbon cartridge
- » 16-digit LCD display
- » Windows® drivers for 2000 and XP
- » One year printer warranty
- » One year (unlimited passes) printhead warranty

Printing

- » Color dye sublimation or monochrome thermal transfer printing
- » 30 seconds per card full-color single-sided (YMCKO)
- » 35 seconds per card full-color dual-sided (YMCKOK)
- » 300 dpi (11.8 dots/mm) print resolution

Bar Codes

- » Code 39, Code 128 B & C with & without check digit
- » 2 of 5 & 2 of 5 Interleaved
- » UPC-A, EAN 8 & EAN 13
- » PDF-417 2D bar code and other symbologies can be printed via Windows drivers

Card Specifications

- » Types: PVC, PVC Composite.
- » Card width/length: ISO CR-80-ISO 7810, 2.12" (54mm) x 3.38" (86mm)
- » Magnetic Stripe-ISO 7811
- » Smart Card-ISO 7816-2
- » Card thickness: 30 mil (.76mm)
- » Card feeder capacity: 100 cards (30 mil)
- » Card output hopper capacity: 45 cards (30 mil)

Communications Interface

- » USB 1.1 (cable included)

Ribbon Specifications*

- » Load-N-Go™ ribbon cartridge with integrated card-cleaning roller
- » i Series technology
- » YMCKO: 200 cards/cartridge
- » YMCKOK: 165 cards/cartridge
- » Monochrome: 1000 cards/cartridge in black, blue, or white

*for optimum printer performance use Genuine Zebra Supplies



Mechanical

- » Width: 7.9 in (201mm)
- » Depth: 12.9 in (328 mm)
- » Height: 8.5 in (216 mm)
- » Weight: 9.5 lbs (4.3 kg)

Electrical

- » 110 ~ 240 Volts AC, 50 ~ 60 Hz (auto switching)
- » 16MB image memory standard
- » FCC Class B, CE, UL and CUL approved

Environmental

- » Operating Temperature: 60°F to 86°F (15°C to 30°C)
- » Operating Humidity: 20% to 65% non-condensing
- » Storage Temperature: 23°F to 158°F (-5°C to 70°C)
- » Storage Humidity: 20% to 70% non-condensing
- » Ventilation: Free air

Options

- » Magnetic encoder (30 mil cards only), 3 track HiCo/LoCo
- » CardSense™ single-feed kit
- » Starter Kit (200 - 30 mil PVC cards and 1 YMCKOK ribbon)
- » Cleaning Kit (4 print engine and 4 feeder cleaning cards)

Genuine Zebra Supplies

- » Your choice of card printer supplies is critical. It is a primary factor affecting the reliability and consistency of printing. Genuine Zebra Supplies meet stringent quality standards and are tested for optimum performance with Zebra card printers.

www.zebracard.com



Zebra Technologies Corporation



An ISO 9001 registered company ©2005 ZIH Corp.
Specifications listed are for base model printers with standard features only unless otherwise notes. Specifications subject to change without notice. All product and brand names are trademarks of their respective companies. All rights reserved. All Copyrights, Trade and Service Marks shown or depicted herein are registered by their owners. No infringement is made for or implied by the use thereof. For more information please contact our authorized partner.
Part No. P120i-08/05

North America

**Zebra Technologies Corporation
Card Printer Solutions**
1001 Flynn Road
Camarillo, CA 93012-8706
USA
Telephone: +1 805 579 1800
Fax: +1 805 579 1808
Toll free in US: 800 452 4056
e-mail: cards@zebra.com

Europe, Middle East, Africa

**Zebra Technologies Corporation
Card Printer Solutions**
The Valley Centre, Gordon Road
High Wycombe
Buckinghamshire HP13 6EQ, UK
Telephone: +44 870 241 1527
Fax: +44 870 241 0765
e-mail: eurosales@zebra.com

Asia Pacific

**Zebra Technologies Corporation
Card Printer Solutions**
16 New Industrial Road
#05-03 Hudson TechnoCentre
Singapore 536204
Telephone: +65 6858 0722
Fax: +65 6885 0836
e-mail: asiasales@zebra.com

Latin America

**Zebra Technologies Corporation
Card Printer Solutions**
9800 NW 41st Street, Suite 220
Doral, FL 33178
USA
Telephone: +1 305 558 3100
Fax: +1 305 558 8485
e-mail: latinsales@zebra.com