SECURITY



Adding unique security features to ID cards is easier, faster, more economical with Zebra's P640i. This next generation printer from Zebra delivers mission-critical reliability and superior affordability. Protect your ID cards from counterfeiting, alteration or duplication with the P640i's customizable levels of security. Zebra is one of the first manufacturers to offer an extended range of security options for all printing components - cards, ribbons, laminates and printers. When security counts, count on Zebra.

Use the P640i printer for:

- » Agency Licenses
- High Security Access Control ID Cards
- Law Enforcement and Correctional Facility ID Cards
- Airport ID Cards
- » Any card application requiring long lasting, secure issuance of tamper-resistant ID's

Many "Best In Class" features:

- Lowest consumables cost per card in the industry
- » Highest production output speed with continuous card loading feature.
- Superior print quality for optimal color fidelity and precision details
- » Reliable and easy to use

Key Features

- » Full Color Dual-Sided Card Printing and Dual-Sided Lamination
- » Micro Card Positioning for **Excellent Color Registration** and Superior Print Quality
- » Numerous Security Features (covert printing, Secure ID/Key, ID/Log)
- » Built-in Ethernet for Network Capability (optional)





P640i

Card Printer Product Specifications



General Specifications

- » Dual-sided printing and one-pass waste-free lamination
- » 120 cards/hour dual-sided printing and laminating (YMCK ribbon & 1.0 mil laminate both sides)
- » Micro-positioning card transport system for enhanced color photos
- » Complete system security features & options for printer, ribbons, laminate, cards, and card issuance process
- » Covert printing capability text approx 17 mil high
- » Automated card cleaning before printing
- » Built-in Ethernet option for networking capability
- » Windows® drivers for 2000 and XP with advanced security features (ID/Log & password protection)
- » One year printer warranty
- » One year (unlimited passes) printhead warranty

Color Printing

- » Color dye sublimation and resin K
- » 30 seconds per card (YMCK & dual sided lamination)
- » 300 dpi (11.8 dots/mm) print resolution

Bar Codes

» Bar codes and other symbologies available via Windows driver

Fonts

» True Type or other type fonts via Windows driver

Card Specifications

- » Types: PVC Composite
- » Card width/length: ISO CR-80 ISO 7810 2.12" (54mm) x 3.38" (86mm)
- » HiCo Magnetic Stripe ISO 7811
- » Contact Smart Card ISO 7816 Compliant
- » Contactless Smart Card Mifare® or HID iClass™
- » Card thickness: 27 mil 39 mil
- » Card input hopper capacity: 150 cards

Ribbon Specifications

» YMCK: 600 cards/roll» YMCKK: 500 cards/roll

» YMCUvK: 500 cards/roll

www.zebracard.com

» Cleaning cartridge: cleans 3,000+ cards



Laminate Specifications

- » Linerless & wastefree 1.0 mil laminate, 600 cards/roll
- » 2 Laminate cassettes (upper & lower)
- » Laminates available:

Clear full size, clear for magnetic stripe cards and clear for smart cards. Custom laminates available upon request:

Holographic images Special OVD images UV images

Communications Interface

- » USB 1.1 (Standard)
- » Factory Installed Options

Built-In Ethernet

Bi-directional Parallel with ECP support

Mechanical

» Width: 27.5" (699mm) not including exit hopper

» Depth: 9.7" (246mm)» Height: 11.5" (292mm)» Weight: 35 lbs (15.9kg)

Electrical

- » 110 240 Volts AC, 50/60 Hz
- » FCC Class A, UL, CUL, & CE approved

Environmental

- » Operating temperature: 50°F to 95°F (10°C to 35°C)
- » Operation humidity: 20% to 80% non-condensing
- » Storage temperature: -4°F to 158°F (-20°C to 70°C)
- » Storage humidity: 5% to 90% non-condensing
- » Ventilation: Free air

Options

- » ID/Key security printing feature
- » Magnetic Encoder
- » Smart Card Contact Station
- » Smart Card Contactless encoder/reader
- » Smart Card Contact encoder/reader
- » Warranty programs

Optimized for use with Zebra media

Zobra Zebra Technologies Corporation ISO 9001

An ISO 9001 registered company ©2004 ZIH Corp. Specifications listed are for base model printers with standard features only unless otherwise notes. Specifications subject to change without notice. All product and brand names are trademarks of their respective companies. All rights reserved. All Copyrights, Trade and Service Marks shown or depicted herein are registered by their owners. No infringement is made for or implied by the use thereof. For more information, Part No. P640i - 11/04 please contact our authorized partner.

North America

Zebra Technologies Corporation Card Printer Solutions

1001 Flynn Road Camarillo, CA 93012-8706 USA

Telephone: +1 805 579 1800 Fax: +1 805 579 1808 Toll free in US: 800 452 4056 e-mail: cards@zebra.com

Europe, Middle East, Africa

Zebra Technologies Corporation Card Printer Solutions

The Valley Centre, Gordon Road High Wycombe Buckinghamshire HP13 6EQ, UK Telephone: +44 870 241 1527 Fax: +44 870 241 0765 e-mail: eurosales@zebra.com

Asia Pacific

Zebra Technologies Corporation Card Printer Solutions

16 New Industrial Road #05-03 Hudson TechnoCentre Singapore 536204 Telephone: +65 6858 0722 Fax: +65 6885 0836 e-mail: asiasales@zebra.com

Latin America

Zebra Technologies Corporation Card Printer Solutions

9800 NW 41st Street, Suite 220 Doral, FL 33178 USA Telephone: +1 305 558 3100

Telephone: +1 305 558 3100 Fax: +1 305 558 8485 e-mail: latinsales@zebra.com